



RISE AUDIO



LA206

产品说明书

LA206 专业音响 PROFESSIONAL AUDIO




固定安装 Application and installation




结构图纸 Construction Drawing:


外观设计可能有所改变
Cosmetic change may be made



主视图



后视图



侧视图



顶视图

技术指标 Technical data & Inteoduction:

型号: LA206

单元类型: 2 x 6" LF / 1 x 1.75" HF

频率范围 (±3dB): 60-20000Hz

额定功率 (节目/峰值): 400/800W(passiv)

300/600W(biamped LF)

80/160(biamped HF)

阻抗: passive 16 Ohm

biamped LF 16 Ohm

biamped HF 8 Ohm

覆盖角度 (水平×垂直): 80° or 120°×10°

灵敏度1W/1M :114dB passive 8 Ohm

103dB(biamped LF)

111dB(biamped HF)

最大声压级 (1M): 126dB

外形尺寸 (高×宽×深): 180×590×300 mm

重量: 12.9kg/13.5kg(带分频版)

涂层: 聚酯喷漆

可选项: PwLA10内置分频版, 主动/被动模式

可切换RAL颜色可选 (Warnex结构漆)

Model: LA206

Drivers: 2 x 6" LF / 1 x 1.75" HF

Frequency range: 60 - 20000 Hz

Power capacity programm / peak: 400 / 800 W biamped LF

300 / 600 W biamped HF

80 / 160 W, passive

Impedance: 16 ohms biamped LF

8 ohms biamped HF

16 ohms passive

Coverage range (h x v): 80° or 120° x 10°

Sensitivity 1 W / 1 m: 104 dB biamped LF

112 dB biamped HF

114 dB passive

SPLmax / 1 m / peak: 133 dB

Dimensions (h x w x d): 180 x 590 x 300 mm

Weight: 12.9 kg / 13.5 kg with passive crossover

Finish: polyurethane coating

Options: LA10 internal passive crossover switchable

bet- ween active and passive mode, RAL colours

博天下之銳意
展妙韻之升華



锐昇(博锐韵声)音响

广州锐昇(博锐韵声)音响设备有限公司

电话: 020-34560685

网址: <http://www.rise-audio.com>

地址: 广州市番禺区钟村镇新六亩路5号

颠覆娱乐行业的先行者!