





LA208

产品说明书

LA208 专业音响 PROFESSIONAL AUDIO




固定安装 Application and installation




结构图纸 Construction Drawing:


外观设计可能有所改变
Cosmetic change may be made




主视图



后视图



侧视图



顶视图

技术指标 Technical data & Introduction:

型号: LA208

单元类型: 2 x 8" LF / 1 x 1.73" HF

频率范围 (±3dB): 60-20000Hz

额定功率 (节目/峰值): 800/1600W (passive)

400/800W (biamped LF)

80/160 (biamped HF)

阻抗: passive 16 Ohm

biamped LF 16 Ohm

biamped HF 8 Ohm

覆盖角度 (水平×垂直): 80° or 120° × 10°

灵敏度 1W/1M: 113dB passive 8 Ohm

101dB (biamped LF)

110dB (biamped HF)

最大声压级 (1M): 128dB

外形尺寸 (高×宽×深): 250×750×305 mm

重量: 16.9kg / 18kg (带分频版)

涂层: 聚酯喷漆

可选项: PWLA10 内置分频版, 主动/被动模式

可切换 RAL 颜色可选 (Warnex 结构漆)

Model: LA208

Drivers: 2 x 8" LF / 1 x 1.75" HF

Frequency range: 60 - 19000 Hz

Power capacity program / peak: 400 / 800 W biamped LF

800 / 160 W biamped HF

800 / 1600 W, passive

Impedance: 16 ohms biamped LF

8 ohms biamped HF

16 ohms passive

Coverage range (h x v): 80° or 120° × 10°

Sensitivity 1 W / 1 m: 101 dB biamped LF

110 dB biamped HF

113 dB passive

SPL max / 1 m / peak: 128 dB

Dimensions (h x w x d): 250 x 750 x 305 mm

Weight: 16,9 kg / 18 kg with passive crossover

Finish: polyurethane coating

Options: PWLA10 internal passive crossover switchable

bet-ween active and passive mode, RAL colours

博天下之銳意
展妙韻之升華



锐昇(博锐韵声)音响

广州锐昇(博锐韵声)音响设备有限公司

电话: 020-34560685

网址: <http://www.rise-audio.com>

地址: 广州市番禺区钟村镇新六亩路5号

颠覆娱乐行业的先行者!