



RISE AUDIO



RH515

产品说明书


RH515 专业音响 PROFESSIONAL AUDIO




固定安装 Application and installation




结构图纸 Construction Drawing:



主视图




后视图



侧视图



底视图



顶视图

外观设计可能有所改变
Cosmetic change may be made

技术指标 Technical data & Inteoduction:

型号 Model	RH515	
类型 TYPE	COMPACT, TWO-WAY PASSIVE 紧凑两频全频	
单元组成 Drivers	LF:1X15"(380mm)/3"(75mm)Voice-coil HF:1X1.75"(45mm)exit/3"(75mm)Voice-coil	
频率响应 (+/-3dB) Frequency Response(+/-3dB)	55-19000Hz	
覆盖角度 (-6dB) Dispersion(-6dB)	90x50(可旋转)	
灵敏度 (1m/1W) Sensitivity(1m/1W)	102dB	
输出声压级 maximum SPL	129.4dB continuous/135.4dB	
额定阻抗 Nominal Impedance	8.Ohms	
功率 Rated Power	500W AES / 2000W PEAK	
推荐放大器功率 Recommended AMP	800W-1100W@8 Ohms	
分频点 Crossover Frequency	1800Hz	
输入连接器 Connectors	2x Neutrik NI4MP	
产品尺寸 (HxWxD) Dimensions (HxWxD)	750mm x 450mm x 459mm	
包装尺寸 (HxWxD) Packing Dimensions (HxWxD)	765mm x 460mm x 480mm	
净重量 Net Weight	32kg	
包装总重量 Gross Weight	34kg	
箱体材料 Enclosure Material	优质高密度夹板	
箱体网面 Enclosure Material	外透特制网峰, 内透圆形网	
表面喷涂 Finish	黑色耐磨环保水性阻燃漆喷料 (可定制颜色)	
吊装点 Hanging Position	16个 M8螺丝吊装孔位	
支撑座 Pole Mount	合金材质@35毫米标准底部支撑座	
适用范围 Applications	音乐厅, 多功能厅, 礼堂, 礼堂	

博天下之銳意
展妙韻之升華



锐昇(博锐韵声)音响

广州锐昇(博锐韵声)音响设备有限公司

电话: 020-34560685

网址: <http://www.rise-audio.com>

地址: 广州市番禺区钟村镇新六亩路5号

颠覆娱乐行业的先行者!