






RH915

产品说明书


RH915 专业音响 PROFESSIONAL AUDIO




固定安装 Application and installation



结构图纸 Construction Drawing:




主视图




后视图



侧视图



底视图



顶视图

外观设计可能有所改变
Cosmetic change may be made

技术指标 Technical data & Inteoduction:

型号 Model	RH915
类型 TYPE	COMPACT, TWO-WAY PASSIVE 紧凑两分频全频
单元组成 Drivers	LF:1X15" (380mm) / 3" (75mm) Voice-coil HF:1X1" (26mm) exit / 1.75" (44mm) Voice-coil
频率响应 (+/-3dB) Frequency Response (+/-3dB)	550-19000Hz
覆盖角度 (-6dB) Dispersion (-6dB)	80x60 (可旋转)
灵敏度 (1m/1W) Sensitivity (1m/1W)	103dB
输出声压级 maximum SPL	129.4dB continuous / 136.4dB
额定阻抗 Nominal Impedance	8 Ohms
功率 Rated Power	500W AES / 2000W PEAK
推荐放大器功率 Recommended AMP	800W-1100W @ 8 Ohms
分频点 Crossover Frequency	1800Hz
输入连接器 Connectors	2x Neutrik NI4MP
产品尺寸 (HxWxD) Dimensions (HxWxD)	690mm x 470mm x 445mm
包装尺寸 (HxWxD) Packing Dimensions (HxWxD)	705mm x 480mm x 455mm
净重量 Net Weight	36 kg
包装总重量 Gross Weight	40kg
箱体材料 Enclosure Material	优质高密度优质夹板
箱体网面 Enclosure Material	外透特制网棉, 内圆形钢网
表面喷涂 Finish	黑色耐磨环氧水性阻燃漆喷料 (可定制颜色)
吊装点 Hanging Position	15个 M8 螺丝吊装孔位 及 4个 铝合金吊架座
支撑座 Pole Mount	合金材质 @ 35 毫米标准底部支撑座
适用范围 Applications	音乐厅, 多功能厅, 礼堂, 会议室

博天下之銳意
展妙韻之升華



锐昇(博锐韵声)音响

广州锐昇(博锐韵声)音响设备有限公司

电话: 020-34560685

网址: <http://www.rise-audio.com>

地址: 广州市番禺区钟村镇新六亩路5号

颠覆娱乐行业的先行者!